


Features

- Bidirectional Protection
- Fast Response Time : Typically < 1ns
- Excellent Clamping Capability
- Low clamping voltage
- Built-in Strain relief
- Low inductance
- Low profile package
- High temperature solder:260°C/10 seconds at terminal
- IEC 61000-4-2 (ESD) ±30kV(air), ±30kV(contact)



Mechanical Characteristics


- SOD-123 package
- Matte tin lead - free plated
- Marking: Marking Code
- RoHS Compliant

Applications

- I/O Interfaces
- Power lines
- Automotive and Telecommunication
- Industrial Electronics


Absolute Maximum Rating			
Rating	Symbol	Value	Units
Peak pulse power (8/20μs)	P _{PP}	5000	W
Peak pulse current (8/20μs)	I _{PP}	150	A
Operating Junction Temperature range	T _J	-55 to + 150	°C
Storage Temperature range	T _{STG}	-55 to + 150	°C

Pin Configuration



Electrical Characteristics

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current



Electrical Characteristics

WS24P4S1-B						
Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Units
Reverse Stand-Off Voltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	26.7		29.5	V
Reverse Leakage Current	I_R	$V_{RWM}=24V, T=25^{\circ}C$			1	μA
Clamping Voltage	V_C	$I_{PP}=150A, t_p=8/20\mu s$			35.0	V
Junction Capacitance	C_j	$V_{BIAS}=0V, f=1MHz$		320		pF

Typical Characteristics

Figure 1: Peak Pulse Power Rating Curve




Figure 2: Pulse Derating Curve




Figure 3: 8/20µs Pulse Waveform






Figure 4: Clamping Voltage Curve(8/20µs, 2 Ω)




Outline Drawing – SOD-123

Ref. (mm)	Millimeters	
	Min.	Max.
A	2.50	2.90
B	3.40	3.90
C	0.70	1.10
D	1.50	1.80
E	0.45	0.95
F	0.05	0.26
G	0.90	1.20



Recommended Solder Pad Layout



Dimensions in mm

Marking Code



Package Information

Package Type	Description	Quantity (pcs)
SOD-123	Tape & Reel -8mm/7" tape	3000

Contact Information

CYG WAYON CIRCUIT PROTECTION CO., LTD.

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207
 Tel: +86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com
 WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

CYWAYON® is registered trademarks of Wayon Corporation.

Specifications are subject to change without notice.
 The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
 Users should verify actual device performance in their specific applications.